



Printer for  
Shimadzu Electronic Balances

# EP-80



Printer for  
Shimadzu Electronic Balances

# EP-90



# EP-80

## Printer for Shimadzu Electronic Balances

Useful with a variety of Shimadzu electronic balances Easily connects to a balance using the provided cable

- Dot impact printer uses standard paper, making long-term storage easy
- High-speed printing performance of approx. 3 rows/second
- Thick roll paper reduces need for troublesome paper replacement. (30 m, can print approx. 8000 lines)
- Equipped with newly developed ergonomic-design push buttons
- Also uses dry cell batteries (6 AA)
- WindowsDirect function compatibility
- Print calibration results by connecting to a balance equipped with ISO print functionality
- Includes statistic calculation functions
- Can turn ON/OFF the balance's autoprnt function



# EP-90

## Printer for Shimadzu Electronic Balances

Can simultaneously print date, time and sample number for each set of measurement data Easily turn ON/OFF the balance applications/functions from the printer

- This model augments EP-80 functionality with the following additional functions
- Simultaneous printing of date, time\*1, ID, and sample numbers together with measurement results
- Automatic incrementation of sample numbers
- Multiplication function
- Comparator function
- Easily turn ON/OFF a variety of balance applications/functions, such as loading, live animal measurement, and %.

\*1: Date and time printout is performed using data from the balance's internal clock. Printout of this data is not possible if the balance does not have a built-in clock.

Print Method	Dot impact
Inking	Ink ribbon (purple color)
Print Format	24 digits/line (5 x 7 dot matrix)
Print Speed	2.7 lines/sec. (mechanical printing performance)
Character Size	Approx. 1.7 mm (W) x 2.6 mm (H)
Printer Paper	Standard paper 57.5 mm (W) (30 m, for approx. 8,000 lines)
Printer Mechanism Durability	1.5 million lines
Operating Temperature	5 °C to 40 °C
Power Source	AC adaptor (9 V DC/2 A) or alkaline dry cells (6 AA batteries) Battery life: Approx. 10 hours (printing 1 line/5 sec.)
Interface	Serial I/O TTL level
Dimensions	154 mm (W) x 215 mm (D) x 78.5 mm (H)
Weight	Approx. 630 g
Functions	Statistic calculations (no. of data points, total, maximum value, minimum value, range, average value, standard deviation) Turns ON/OFF balance's autoprnt function PRINT command TARE command WindowsDirect function compatibility
Accessories	AC adaptor, paper roll (1 roll), ink ribbon cartridge (1), connection cable

Printing Method	Dot impact
Inking	Ink ribbon (purple color)
Print Format	24 digits/line (5 x 7 dot matrix)
Print Speed	2.7 lines/second
Character Size	Approx. 1.7 mm (W) x 2.6 mm (H)
Printer Paper	Standard paper 57.5 mm (W) (30 m, for approx. 8,000 lines)
Print Mechanism Durability	1.5 million lines
Operating Temperature	5 °C to 40 °C
Power Source	AC adaptor (9 V DC/2 A) or alkaline dry cells (6 AA batteries) (Approx. 10 hours continuous use, printing 1 line/5 sec.)
Interface	Serial I/O TTL level
Dimensions	154 mm (W) x 215 mm (D) x 78.5 mm (H)
Weight	Approx. 630 g
Functions	Statistic calculations, output (PRINT) command, TARE command, date and time printing* (can be printed automatically for each measurement result, based on the balance's internal clock), ID printing, sample number (automatic incrementation) printing, multiplication, comparator, autoprnt, ON/OFF command for balance applications/functions, WindowsDirect simultaneous output
Accessories	AC adaptor, paper roll (1 roll), ink ribbon cartridge (1), connection cable



SHIMADZU CORPORATION. International Marketing Division

3. Kanda-Nishikicho 1-chome, Chiyoda-ku, Tokyo 101-8448, Japan Phone: 81(3)3219-5641 Fax: 81(3)3219-5710  
Cable Add.: SHIMADZU TOKYO